

511,071

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau




(43) International Publication Date  
6 November 2003 (06.11.2003)

PCT

(10) International Publication Number  
**WO 03/091581 A1**

- (51) International Patent Classification: **F16B 19/10**, B21K 1/60
- (21) International Application Number: PCT/EP03/03651
- (22) International Filing Date: 9 April 2003 (09.04.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 0209143.7 23 April 2002 (23.04.2002) GB
- (71) Applicant (for all designated States except US): **NEWFREY LLC** [US/US]; Drummond Plaza Office Park, 1423 Kirkwood Highway, Newark, DE 19711 (US).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **JONES, Steven, Victor** [GB/GB]; 34 Shenstone Road, Great Barr, Birmingham B43 5LN (GB).
- (74) Agent: **HAAR, Lucas, H.**; Haar & Schwarz-Haar, Lessingstrasse 3, 61231 Bad Nauheim (DE).
- (81) Designated States (national): JP, US.
- (84) Designated States (regional): European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).
- Declaration under Rule 4.17:**  
— as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for the following designations JP, European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR)
- Published:**  
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **BLIND RIVET AND METHOD TO MAKE SAME**



(57) **Abstract:** The invention is directed to a peel-type blind rivet assembly (110) for setting in relatively soft material and comprising an elongate tubular body (102) having a shank (106) with a enlarged head (108). A free end (114) of the shank, remote from the head (108), has an expandable portion formed by a plurality of slots (112) extending partway along the shank from this remote end (114). A mandrel (104) has a stem, and a mandrel head (126) with a maximum external diameter greater than the internal diameter of the body (102), wherein at least one of the plurality of slots (112) increases in width as it extends from an outer surface of the shank towards an inner surface of the shank. There is also provided a punch (280) for forming the tapered slots (112) in the rivet body, comprising an elongate solid body having a polygonal cross section wherein at least one convergence zone formed on an end face of the punch by the tapering convergence of two adjacent side walls forms a slot cutting element (285).

WO 03/091581 A1